

LP12-7.0E (T1)



Specification	
Nominal Voltage	12V
Nominal Capacity(20HR)	7.0AH
Watts(15min Rate)	19.5 Watts at 1.67V/cell
Dimensions	Length 151±2mm (5.94 inches)
	Width 65±1mm (2.54 inches)
	Container Height 93.5±1mm (3.68 inches)
	Total Height (with Terminal) 99±1mm (3.90 inches)
Approx Weight	Approx 1.85 kg (4.08lbs)
Terminal	T1
Container Material	ABS
Rated Capacity	7.0 AH/0.310A (20hr, 1.80V/cell, 25°C/77°F)
	5.37 AH/0.671A (10hr, 1.80V/cell, 25°C/77°F)
	4.88 AH/0.976A (5hr, 1.75V/cell, 25°C/77°F)
	4.50AH/1.50A (3hr, 1.75V/cell, 25°C/77°F)
	3.90 AH/3.90A (1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	93.0A (5s)
Internal Resistance	Approx 28mΩ
Operating Temp. Range	Discharge : -15±50°C (5±122°F)
	Charge : 0±40°C (32±104°F)
	Storage : -15±40°C (5±104°F)
Nominal Operating Temp. Range	25 3°C (77 5°F)
Cycle Use	Initial Charging Current less than 1.86A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C
	Standby Use
Capacity affected by Temperature	40°C (104°F) 103%
	25°C (77°F) 100%
	0°C (32°F) 86%
Self Discharge	Leoch LP series battery may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required.
	For higher temperatures the time interval will be shorter.

Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77 °F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	10.7	8.69	7.14	6.17	4.81	3.64	3.01	1.78	1.36	1.08	0.890	0.765	0.632	0.538	0.307
1.80V/cell	14.3	11.1	8.72	7.36	5.68	4.24	3.37	1.94	1.47	1.15	0.953	0.821	0.671	0.571	0.310
1.75V/cell	16.1	12.2	9.37	7.85	5.90	4.40	3.53	2.01	1.50	1.17	0.976	0.844	0.683	0.576	0.313
1.70V/cell	17.8	13.3	10.0	8.25	6.16	4.55	3.64	2.09	1.54	1.21	1.00	0.861	0.692	0.582	0.319
1.65V/cell	19.6	14.3	10.7	8.76	6.48	4.69	3.76	2.15	1.60	1.25	1.03	0.880	0.703	0.594	0.323
1.60V/cell	21.6	15.6	11.5	9.34	6.84	4.89	3.90	2.22	1.65	1.29	1.05	0.899	0.710	0.600	0.325

Constant Power Discharge (Watts) at 25 °C (77 °F)




F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	19.9	16.3	13.6	11.9	9.34	7.13	5.91	3.51	2.71	2.14	1.78	1.53	1.27	1.08	0.620
1.80V/cell	26.2	20.5	16.3	13.9	10.9	8.23	6.59	3.80	2.90	2.28	1.89	1.64	1.34	1.15	0.624
1.75V/cell	29.2	22.3	17.4	14.7	11.2	8.49	6.86	3.93	2.94	2.32	1.93	1.68	1.36	1.16	0.629
1.70V/cell	31.8	24.1	18.4	15.3	11.6	8.71	7.06	4.08	3.02	2.38	1.97	1.71	1.38	1.17	0.641
1.65V/cell	34.7	25.8	19.5	16.2	12.1	8.91	7.24	4.17	3.13	2.45	2.02	1.74	1.40	1.19	0.649
1.60V/cell	37.9	27.7	20.7	17.1	12.7	9.24	7.46	4.29	3.21	2.52	2.07	1.77	1.41	1.20	0.651




Dimensions

T1 Terminal


Unit: mm




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



- A** No supplementary charge required (Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
 3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this is reached.

Sales Office

China sales office:
 Add: 5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
 Nanshan, Shenzhen, China. 518052
 Tel: +86-755-86036060 (100 lines)
 Fax: +86-755-26067269
 E-mail: export@leoch.com
 Http://www.leoch.com

HongKong sales office:
 Add: Workshop C, 33/F, TML Tower,
 No. 3 Hoi Shing Road, Tsuen Wan,
 New Territories, Hong Kong
 Tel: +852 35786666
 Fax: +852 21170016
 E-mail: sales.hk@leoch.com

Singapore sales office:
 Add: No. 1 Tech Park Crescent,
 Singapore 638131
 Tel: +65 6863 6078 (5 lines)
 Fax: +65 6863 6079
 Email sales.sg@leoch.com

North America sales office:
 Add: 19751 Descartes, Unit A,
 Foothill Ranch, CA 92610, USA
 Tel: 949-588-5853
 Fax: 949-588-5966
 E-mail: sales@leoch.us
 Http://www.leoch.com

Europe sales office:
 Add: 9B Wheatstone Court, Waterwells
 Business Park, Gloucester, GL2-2AQ, UK
 United Kingdom
 Tel: +44(0) 1452 729428 / 1452 729696
 Fax: +44 (0)1452-690125
 E-mail: Sales.Europe@leoch.com